



((() 100V 115/120V 230/240V

Eos® Series





GENERAL INFORMATION

The Eos motorized fader wings may be used to provide extended playbacks for Eos Ti, Gio, Ion, Eos/Ion RPUs, RVIs, ETCnomad (PC or Mac native) and ETCnomad Puck.

Up to three wings may be attached to any of these devices. There are two wings – a x10 and x20. The x10 has 10 60mm motorized faders, two 4.3" full-colour high-resolution displays and three control buttons. The x20 adds 10 additional faders, two more displays and three control buttons. The wing provides power sensing and automatically turns on when both an active USB data connections and mains power are provided via the external 12V power supply.

Connected devices must be running Microsoft Windows 7 or higher or Mac OSX Mavericks or later. These wings are NOT compatible older devices based on Windows XP.

FEATURES

- Playback layout consistent with Eos Ti and Gio
- Either 10 or 20 pageable playbacks (100 pages are supported)
- Paging/bank conventions are determined in a setup menu
- Button/fader and configuration mapping displayed via fullcolor high-resolution displays.
- Two powered USB ports
- VESA 100x100mm mountable
- Kensington Lock compatible attachment point

INTERFACES

- AC Input (100 240VAC at 50/60Hz) with external power supply
- Two USB ports

ORDERING INFORMATION

Eos Motorized Fader Wings

PART NO.	DESCRIPTION	
4240A1022-EU	Eos Motorized Fader Wing 20	
4240A1021-EU	Eos Motorized Fader Wing 10	

Eos Motorized Fader Wing Accessories

PART NO.	DESCRIPTION
4240A1020-EU	Eos Programming Wing
110014	Eos Combined Fader Wing Flight Case (Fits FW and MFW 10 and 20)
ETCnomad (256-6144)	ETCnomad (256-6144 Output Kits)
ETCnomad Puck (256-2048)	ETCnomad Puck (256-2048 Outputs)

Ships with

- Power supply
- IEC power cord set UK13A and Schuko included
- Dust cover
- USB cable

The wing is compatible with

- Eos Ti
- Gio
- Ion
- Eos/Ion Remote Processor Units
- ETCnomad for PC/Mac (requires ETCnomad Lighting Controller Kit and output device)
- ETCnomad Puck

Note: These wings are not supported on Element.



Eos Series

PHYSICAL

Eos Motorized Fader Wing Dimensions*


MODEL	HEIGHT	WIDTH	DEPTH
	mm	mm	mm
Eos MFW 20	109	500	341
Eos MFW 10	109	310	341
Eos PGW with Flight Case	316	802	520

Eos Motorized Fader Wing Weights*


MODEL	WEIGHT	SHIPPING WEIGHT
	kgs	kgs
Eos MFW 20	4.9	7.8
Eos MFW 10	2.8	5.7


^{*}Weights and dimensions typical

EOS MOTORIZED FADER WING 10



EOS MOTORIZED FADER WING 20









Corporate Headquarters ● 3031 Pleasant View Rd, PO Box 620979, Middleton WI 53562 0979 USA ● +1 608 831 4116

London, UK ● Unit 26-28, Victoria Industrial Estate, Victoria Road, London W3 6UU, UK ● +44 (0) 20 8896 1000

Rome, IT ● Via Pieve Torina, 48, 00156 Rome, Italy ● +39 (06) 32 111 683

Holzkirchen, DE ● Ohmstrasse 3, 83607 Holzkirchen, Germany ● +49 (80 24) 47 00-0

Hong Kong ● Room 1801, 18/F, Tower 1 Phase 1, Enterprise Square, 9 Sheung Yuet Road, Kowloon Bay, Kowloon, Hong Kong ● +852 2799 1220