



CE PONY FOLLOW SPOT DMX
5000°K
 Cod. 9818116505

Follow spot with 155W LED source, dmx dimming control, stand alone functions, 8°/22° optics, manual regulation of zoom and focus, complete with color frame, shutter blades, iris diaphragm & dimming shutter.

Control signals: DMX512, WIRELESS DMX (optional). Stand-alone functions with local control of intensity. PWM can be set via display from 300Hz to 4Khz in not even steps. Resolution 8/ 8-11Bit conversion /16 Bit. USB port for software update.



ELECTRICAL DATA

Power supply	100-240Vac 50/60Hz
Max power consumption	0.7 A
Max power	155 W
DMX connection	5 POLES XRL PLUG + RJ 45
Power connection	POWERCON IN&OUT NEUTRIK

OPTICAL DATA

Number and type of LEDs	1 COB BRIDGELUX
Color temperature	5000 °K
CRI min.	90
Optics	8°-22°

MECHANICAL DATA

Painting	BLACK WITH EPOXIDIC POWDER
Net weight	15.5 Kg
Cooling system	AUTOMATIC FAN ASSISTED WITH VARIABLE SPEED

Max noise level

Body	DIE-CAST ALUMINIUM
IP protection rate	IP20

FUNCTIONAL DATA

Working position	+/-45°
Max ambient temperature	35 °C
Thermal protection	ELECTRONIC
Colors and dimmer resolution	8-16 BIT
Stand-alone function	DIMMER
Control signal	DMX 512, WIRELESS DMX(optional)

PHOTOMETRIC DATA at minimum zoom - allo zoom minimo

With focused light beam - Con fascio luminoso a fuoco

Dist. m	5	8	10	12	14	16	18	20
Lux	3837	1499	959	666	489	375	296	240
Diam. m	0,7	1,1	1,4	1,7	1,9	2,2	2,5	2,8

PHOTOMETRIC DATA at maximum zoom - allo zoom massimo

With focused light beam - Con fascio luminoso a fuoco

Dist. m	3	5	7	9	10	12	14	15
Lux	7081	2549	1301	787	637	443	325	283
Diam. m	1,2	1,9	2,7	3,5	3,8	4,6	5,4	5,8