

## ARCHI 40 M (it. 170530)



### Specifiche tecniche

LED type	WHITE 2700 WHITE 4000 WHITE 6500 RED GREEN BLUE AMBER
Number of LEDs	16
Lumen MAX	3500
Lenses	8° 15° 15° x 30° 25° 40° 60°
Control type	Protocol USITT DMX512 - RDM Protocol USITT DMX512 - RDM + Wireless (on request)
Functions	RDM/DRS Wireless DMX receiver
Input range	100 - 240 VAC; 47/63 Hz
Power (W)	35
IP protection rating	IP 67
Sizes l x p x h (mm)	325 x 140 x 153
Weight (Kgs)	2,6
Mounting systems	Surface Truss (optional)

Colour finishing	Grey RAL 9006 (standard) Black RAL 9005 (optional) White RAL 9010 (optional)
Marine Grade treatment	None Yes
Product Category	Spot

## La tua configurazione

LED type	WHITE 2700
Number of LEDs	16
Lumen MAX	3500
Lenses	8°
Control type	Protocol USITT DMX512 - RDM
Input range	100 - 240 VAC; 47/63 Hz
Power (W)	35
IP protection rating	IP 67
Sizes l x p x h (mm)	325 x 140 x 153
Weight (Kgs)	2,6
Mounting systems	Surface
Colour finishing	Grey RAL 9006 (standard)
Marine Grade treatment	None
Product Category	Spot