

## ARCHI 40 WB (it. 170230)



### Specifiche tecniche

LED type	CW+WW (5W)
Number of LEDs	8 White (2700K) + 8 White (6500K)
Lumen MAX	3500
Lenses	8° 15° 15° x 30° 25° 40° 60°
Control type	Protocol USITT DMX512 - RDM Protocol USITT DMX512 - RDM + Wireless (on request)
Functions	RDM/DRS Wireless DMX receiver
Input range	100 - 240 VAC; 47/63 Hz
Power (W)	35
IP protection rating	IP 67
Sizes l x p x h (mm)	325 x 140 x 153
Weight (Kgs)	2,6
Mounting systems	Surface Truss (optional)
Colour finishing	Grey RAL 9006 (standard) Black RAL 9005 (optional) White RAL 9010 (optional)
Marine Grade treatment	None Yes
Product Category	Spot

## La tua configurazione

LED type	CW+WW (5W)
Number of LEDs	8 White (2700K) + 8 White (6500K)
Lumen MAX	3500
Lenses	8°
Control type	Protocol USITT DMX512 - RDM
Input range	100 - 240 VAC; 47/63 Hz
Power (W)	35
IP protection rating	IP 67
Sizes l x p x h (mm)	325 x 140 x 153
Weight (Kgs)	2,6
Mounting systems	Surface
Colour finishing	Grey RAL 9006 (standard)
Marine Grade treatment	None
Product Category	Spot