

ARCHIBAR-i 80 M PLUG-IN 30cm (it.231001)



Compact IP 67 Monochromatic inground LED linear bar PLUG-IN version 30 cm long (on request). Profile in aluminium, sturdy 6 mm thick tempered glass, 3 mm thick satin stainless steel AISI 304 flange. Standard 90 cm. Possibility of manual adjusting the lighting angle at 3°.

Technical Specification

LED type	WHITE 2900 K WHITE 4000 K
Number of LEDs	12
LED expected lifetime (hrs)	90000
Lumen MAX	1600
Lenses	5° 10° 10°x30° 10°x55° 25° 40° 60°
Filters	None f 100°
Connectors and cables	Main Power: 3x1mm cable H07 1mt
Input range	200 - 240 VAC; 47/63 Hz
Power (W)	12
Current	60mA@230VAC
IP protection rating	67
IK grade protection	09
Sizes l x p x h (mm)	410x84x70
Weight (Kgs)	1,4
Mounting systems	Inground
Colour finishing	None
Marine Grade treatment	None Yes
Product Category	Inground

Your Configuration

LED type	WHITE 2900 K
Number of LEDs	12
LED expected lifetime (hrs)	90000
Lumen MAX	1600
Lenses	5°
Filters	None
Input range	200 - 240 VAC; 47/63 Hz
Power (W)	12
Current	60mA@230VAC
IP protection rating	67
IK grade protection	09
Sizes l x p x h (mm)	410x84x70
Weight (Kgs)	1,4
Mounting systems	Inground
Colour finishing	None
Marine Grade treatment	None
Product Category	Inground