

ARCHIBAR-i 80 RGBW 30cm (it.232011)



Compact IP 67 RGBW inground LED linear bar RDM-DMX 30 cm long (on request). Profile in aluminium, sturdy 6 mm thick tempered glass, 3 mm thick satin stainless steel AISI 304 flange. Standard 90 cm. Possibility of manual adjusting the lighting angle at 3°.

Technical Specification

LED type	RGBW
Number of LEDs	11
LED expected lifetime (hrs)	50000
Lumen MAX	1060
Red lumen (lm)	220
Green lumen (lm)	420
Blu lumen (lm)	81
White lumen (lm)	420
Lenses	10° 10°x30° 10°x55° 25° 40° 60°
Filters	None f 100°
Connectors and cables	Main Power: 3x1mm cable H07 1mt DMX signal: 1mt shielded cable bare ends
Control type	Protocol USITT DMX512 - RDM Protocol USITT DMX512 - RDM + Wireless (on request)
Functions	RDM/DRS Wireless DMX receiver
Input range	200 - 240 VAC; 47/63 Hz
Power (W)	14
Current	65mA@230VAC
IP protection rating	67
IK grade protection	09

Sizes l x p x h (mm)	410x84x70
Weight (Kgs)	1,5
Mounting systems	Inground
Colour finishing	None
Marine Grade treatment	None Yes
Product Category	Inground

Your Configuration

LED type	RGBW
Number of LEDs	11
LED expected lifetime (hrs)	50000
Lumen MAX	1060
Red lumen (lm)	220
Green lumen (lm)	420
Blu lumen (lm)	81
White lumen (lm)	420
Lenses	10°
Filters	None
Control type	Protocol USITT DMX512 - RDM
Input range	200 - 240 VAC; 47/63 Hz
Power (W)	14
Current	65mA@230VAC
IP protection rating	67
IK grade protection	09
Sizes l x p x h (mm)	410x84x70
Weight (Kgs)	1,5
Mounting systems	Inground
Colour finishing	None
Marine Grade treatment	None
Product Category	Inground