

## ARCHIBAR-i 80 RGBW 90cm (it.232014)



Compact IP 67 RGBW inground LED linear bar RDM-DMX. Profile in aluminium, sturdy 6 mm thick tempered glass, 3 mm thick satin stainless steel AISI 304 flange. Standard 90 cm. Possibility of manual adjusting the lighting angle at 3°.

### Technical Specification

LED type	RGBW
Number of LEDs	33
LED expected lifetime (hrs)	50000
Lumen MAX	3180
Red lumen (lm)	660
Green lumen (lm)	1260
Blu lumen (lm)	242
White lumen (lm)	1260
Lenses	10° 10°x30° 10°x55° 25° 40° 60°
Filters	None f 100°
Connectors and cables	Main Power: 3x1mm cable H07 1mt DMX signal: 1mt shielded cable bare ends
Control type	Protocol USITT DMX512 - RDM Protocol USITT DMX512 - RDM + Wireless (on request)
Functions	RDM/DRS Wireless DMX receiver
Input range	200 - 240 VAC; 47/63 Hz
Power (W)	40
Current	180mA@230VAC
IP protection rating	67
IK grade protection	09

Sizes l x p x h (mm)	1000x84x70
Weight (Kgs)	3,8
Mounting systems	Inground
Colour finishing	None
Marine Grade treatment	None Yes
Product Category	Inground

## Your Configuration

LED type	RGBW
Number of LEDs	33
LED expected lifetime (hrs)	50000
Lumen MAX	3180
Red lumen (lm)	660
Green lumen (lm)	1260
Blu lumen (lm)	242
White lumen (lm)	1260
Lenses	10°
Filters	None
Control type	Protocol USITT DMX512 - RDM
Input range	200 - 240 VAC; 47/63 Hz
Power (W)	40
Current	180mA@230VAC
IP protection rating	67
IK grade protection	09
Sizes l x p x h (mm)	1000x84x70
Weight (Kgs)	3,8
Mounting systems	Inground
Colour finishing	None
Marine Grade treatment	None
Product Category	Inground