

ARCHIBAR SL150 RGBW 150 cm (it. 184017)



Technical Specification

LED type	RGBW5050MULTICHIP
Number of LEDs	20
LED expected lifetime (hrs)	50000
Lumen MAX	7090
Red lumen (lm)	1300
Green lumen (lm)	3070
Blu lumen (lm)	440
White lumen (lm)	2700
Lenses	8° 15° 15° x 30° 25° 40° 60°
Filters	None f 17° f 34° f 8°x 60°
Control type	Protocol USITT DMX512 - RDM Protocol USITT DMX512 - RDM + Wireless (on request)
Functions	RDM/DRS Wireless DMX receiver
Input range	100 - 240 VAC; 47/63 Hz
Power (W)	110W
IP protection rating	IP 67
Sizes l x p x h (mm)	1484 x 93 x 115 mm
Weight (Kgs)	xxx

Mounting systems	Surface Truss (optional)
Colour finishing	Grey RAL 9006 (standard) Black RAL 9005 (optional) White RAL 9010 (optional)
Marine Grade treatment	None Yes
Product Category	Linear Bar

Your Configuration

LED type	RGBW5050MULTICHIP
Number of LEDs	20
LED expected lifetime (hrs)	50000
Lumen MAX	7090
Red lumen (lm)	1300
Green lumen (lm)	3070
Blu lumen (lm)	440
White lumen (lm)	2700
Lenses	8°
Filters	None
Control type	Protocol USITT DMX512 - RDM
Input range	100 - 240 VAC; 47/63 Hz
Power (W)	110W
IP protection rating	IP 67
Sizes l x p x h (mm)	1484 x 93 x 115 mm
Weight (Kgs)	xxx
Mounting systems	Surface
Colour finishing	Grey RAL 9006 (standard)
Marine Grade treatment	None
Product Category	Linear Bar

ARCHILED 200 RGBWA (it.170110)



Technical Specification

LED type	RGBWA
Number of LEDs	26
LED expected lifetime (hrs)	50000
Lumen MAX	6800
Red lumen (lm)	1300
Green lumen (lm)	3000
Blu lumen (lm)	400
White lumen (lm)	2500
Amber lumen (lm)	1300
Lenses	8° 15° 15° x 30° 25° 40° 60°
Filters	None f 60° f 100° f 8°x 60°
Connectors and cables	Main Power: 3x1mm cable H05 1,5mt DMX signal: IN/OUT cable 0,3mt. + 4pin connectors IP67 (male-female)
Control type	Protocol USITT DMX512 - RDM Protocol USITT DMX512 - RDM + Wireless (on request)

Functions	LED display with flip function Dedicated DMX channel for white balance from 2000K to 10000K DMX or Auto Mode with Master-Slave function Intelligent temperature control Continuous dimming 0-100% Smooth dimming function Halogen simulation CYM simulation Flicker-free function
Setup	RDM/DRS + touch control panel
DMX channels	10ch - 7ch - 6ch - 5ch
Input range	100 - 277 VAC; 47/63 Hz
Power (W)	80W
Current	0,35A@230V
Inrush current	50A@230V
IP protection rating	IP 67
Operating temperature	-30°C +45°C
Sizes l x p x h (mm)	270 x 100 x 303
Weight (Kgs)	4,9
Materials	Ultra clear 4mm tempered glass PMMA lenses Aluminium alloy housing Polyester powder coated
Mounting systems	Surface Truss (optional)
Colour finishing	Black RAL 9005 (standard) Grey RAL 9006 (optional) White RAL 9010 (optional)
Marine Grade treatment	None Yes
Product Category	Spot
Accessories - Flight case	None Yes
Accessories - Anti glare	None Yes
Accessories - Barn door	None Yes

Your Configuration

LED type	RGBWA
Number of LEDs	26
LED expected lifetime (hrs)	50000
Lumen MAX	6800
Red lumen (lm)	1300
Green lumen (lm)	3000
Blu lumen (lm)	400
White lumen (lm)	2500
Amber lumen (lm)	1300
Lenses	8°
Filters	None
Control type	Protocol USITT DMX512 - RDM
Input range	100 - 277 VAC; 47/63 Hz
Power (W)	80W
Current	0,35A@230V
Inrush current	50A@230V
IP protection rating	IP 67
Operating temperature	-30°C +45°C
Sizes l x p x h (mm)	270 x 100 x 303
Weight (Kgs)	4,9
Mounting systems	Surface
Colour finishing	Black RAL 9005 (standard)
Marine Grade treatment	None
Product Category	Spot
Accessories - Flight case	None
Accessories - Anti glare	None
Accessories - Barn door	None