

ARCHIBAR SL250 RGBW 150cm (it.220517)



Specifiche tecniche

LED type	RGBW5050MULTICHIP
Number of LEDs	25
LED expected lifetime (hrs)	50000
Lumen MAX	16100
Red lumen (lm)	3400
Green lumen (lm)	6100
Blu lumen (lm)	1050
White lumen (lm)	6600
Lenses	8° 15° 15° x 30° 25° 40° 60°
Filters	None f 60° f 100° f 8°x 60°
Connectors and cables	Main Power: 3pin IP67 (male-female) DMX signal: 4pin IP67 connector (male-female)
Control type	Protocol USITT DMX512 - RDM Protocol USITT DMX512 - RDM + Wireless (on request)

Functions	LED display with flip function Dedicated DMX channel for white balance from 2900K to 13000K DMX or Auto Mode with Master-Slave function Intelligent temperature control Continuous dimming 0-100% Smooth dimming function Halogen simulation CYM simulation Flicker-free function
Setup	RDM/DRS + touch control panel
DMX channels	9ch - 5ch - 4ch
Input range	100 - 240 VAC; 47/63 Hz
Power (W)	190
Current	0,85A@230V
Inrush current	60A@230V
IP protection rating	IP 67
Operating temperature	-30°C +45°C
Sizes l x p x h (mm)	1517 x 163 x 160
Weight (Kgs)	9,9
Mounting systems	Surface Truss (optional)
Colour finishing	Grey RAL 9006 (standard) Black RAL 9005 (optional) White RAL 9010 (optional) Any RAL (optional)
Marine Grade treatment	None Yes
Product Category	Linear Bar

La tua configurazione

LED type	RGBW5050MULTICHIP
Number of LEDs	25
LED expected lifetime (hrs)	50000
Lumen MAX	16100
Red lumen (lm)	3400
Green lumen (lm)	6100
Blu lumen (lm)	1050
White lumen (lm)	6600
Lenses	8°
Filters	None
Control type	Protocol USITT DMX512 - RDM
Input range	100 - 240 VAC; 47/63 Hz
Power (W)	190
Current	0,85A@230V
Inrush current	60A@230V
IP protection rating	IP 67
Operating temperature	-30°C +45°C
Sizes l x p x h (mm)	1517 x 163 x 160
Weight (Kgs)	9,9
Mounting systems	Surface
Colour finishing	Grey RAL 9006 (standard)
Marine Grade treatment	None
Product Category	Linear Bar