

## ARCHIBAR SL250 RGBW 90cm (it.220514)



### Specifiche tecniche

LED type	RGBW5050MULTICHIP
Number of LEDs	15
LED expected lifetime (hrs)	50000
Lumen MAX	9650
Red lumen (lm)	2050
Green lumen (lm)	3650
Blu lumen (lm)	630
White lumen (lm)	3950
Lenses	8° 15° 15° x 30° 25° 40° 60°
Filters	None f 60° f 100° f 8°x 60°
Connectors and cables	Main Power: 3pin IP67 (male-female) DMX signal: 4pin IP67 connector (male-female)
Control type	Protocol USITT DMX512 - RDM Protocol USITT DMX512 - RDM + Wireless (on request)
Functions	RDM/DRS + touch control panel Wireless DMX receiver

Functions	<p>LED display with flip function  Dedicated DMX channel for white balance from 2900K to 13000K  DMX or Auto Mode with Master-Slave function  Intelligent temperature control  Continuous dimming 0-100%  Smooth dimming function  Halogen simulation  CYM simulation  Flicker-free function</p>
Setup	RDM/DRS + touch control panel
DMX channels	9ch - 5ch - 4ch
Input range	100 - 240 VAC; 47/63 Hz
Power (W)	115 W
Current	0,5A@230VAC
Inrush current	60A@230V
IP protection rating	IP 67
Operating temperature	-30°C +45°C
Sizes l x p x h (mm)	925 x 163 x 160
Weight (Kgs)	6,7
Mounting systems	<p>Surface  Truss (optional)</p>
Colour finishing	<p>Grey RAL 9006 (standard)  Black RAL 9005 (optional)  White RAL 9010 (optional)  Any RAL (optional)</p>
Marine Grade treatment	<p>None  Yes</p>
Product Category	Linear Bar

## La tua configurazione

LED type	RGBW5050MULTICHIP
Number of LEDs	15
LED expected lifetime (hrs)	50000
Lumen MAX	9650
Red lumen (lm)	2050
Green lumen (lm)	3650
Blu lumen (lm)	630
White lumen (lm)	3950
Lenses	8°
Filters	None
Control type	Protocol USITT DMX512 - RDM
Input range	100 - 240 VAC; 47/63 Hz
Power (W)	115 W
Current	0,5A@230VAC
Inrush current	60A@230V
IP protection rating	IP 67
Operating temperature	-30°C +45°C
Sizes l x p x h (mm)	925 x 163 x 160
Weight (Kgs)	6,7
Mounting systems	Surface
Colour finishing	Grey RAL 9006 (standard)
Marine Grade treatment	None
Product Category	Linear Bar