

## ARCHILED 400 RGBWA (it.220210)



### Specifiche tecniche

LED type	RGBWA
Number of LEDs	30
LED expected lifetime (hrs)	50000
Lumen MAX	14900
Red lumen (lm)	2700
Green lumen (lm)	5150
Blu lumen (lm)	820
White lumen (lm)	5150
Amber lumen (lm)	1900
Lenses	6° 10° 25° 40° 60°
Filters	None f 60° f 100° f 6°x 60°
Connectors and cables	Main Power: connettore 4pin IP67 (maschio-femmina) DMX signal: 4pin IP67 connector (male-female)
Control type	Protocol USITT DMX512 - RDM Protocol USITT DMX512 - RDM + Wireless (on request)

Functions	<p>LED display with flip function  Dedicated DMX channel for white balance from 2000K to 10000K  DMX or Auto Mode with Master-Slave function  Intelligent temperature control  Continuous dimming 0-100%  Smooth dimming function  Halogen simulation  CYM simulation  Flicker-free function</p>
Setup	RDM/DRS + touch control panel
DMX channels	10ch - 7ch - 6ch - 5ch
Input range	200 - 240 VAC; 47/63 Hz
Power (W)	210
Current	0,9A@230VAC
Tilt	160°
IP protection rating	IP 67
Operating temperature	-30°C +45°C
Sizes l x p x h (mm)	400 x 125 x 420
Weight (Kgs)	11,5
Materials	<p>Ultra clear 4mm tempered glass  PMMA lenses  All aluminium alloy  Polyester powder coated</p>
Mounting systems	<p>Surface  Truss (optional)</p>
Colour finishing	<p>Black RAL 9005 (standard)  Grey RAL 9006 (optional)  White RAL 9010 (optional)  Any RAL (optional)</p>
Marine Grade treatment	<p>None  Yes</p>
Product Category	Spot
Accessories - Anti glare	<p>None  Yes</p>
Accessories - Barn door	<p>None  Yes</p>

## La tua configurazione

LED type	RGBWA
Number of LEDs	30
LED expected lifetime (hrs)	50000
Lumen MAX	14900
Red lumen (lm)	2700
Green lumen (lm)	5150
Blu lumen (lm)	820
White lumen (lm)	5150
Amber lumen (lm)	1900
Lenses	6°
Filters	None
Control type	Protocol USITT DMX512 - RDM
Input range	200 - 240 VAC; 47/63 Hz
Power (W)	210
Current	0,9A@230VAC
Tilt	160°
IP protection rating	IP 67
Operating temperature	-30°C +45°C
Sizes l x p x h (mm)	400 x 125 x 420
Weight (Kgs)	11,5
Mounting systems	Surface
Colour finishing	Black RAL 9005 (standard)
Marine Grade treatment	None
Product Category	Spot
Accessories - Anti glare	None
Accessories - Barn door	None