



art. 1545

Short description

Reliability and energy efficiency combined with lightness, are the main characteristics of CL-i 40, High Bay for indoor use. It uses high brightness white LEDs in combination with an innovative optical system for a rectangular projection. Easily adaptable for applications such as commercial areas, industrial areas, warehouses and stores where is required widespread and powerful lighting in large spaces.

Standard fixture colour finishing is grey. Optional black and white (art. FX-COLOUR).

Description

• SOURCE

n. 40 (5W) White LEDs (5000K)

On request 3000K, 4000K or 6000K white LEDs

Total light power: 65W

Total out lumen: 10000lm

• OPTIC

35 mm lens Square Opening 20°x30°; (art. 1545)

On request: wide beam lens (art. 1545/w) and narrow beam lens (art. 1545/n)

• CONTROL

None

• CONNECTIONS

Main Power: 3x1mm cable

• SETUP and CONFIGURATION

CL-i 40 (high bay indoor)

Plug-in

- TILT

Manual 30°;

- RATING PROTECTION

IP 20

- POWER SUPPLY

Voltage range: 100-240VAC

Frequency range: 47-63Hz

Active Power factor: PF>0.95/230VAC, PF>0.98/115VAC

Current: 0.35A@230VAC; 0.65A@120V

Fuse inside Power Supply

Power: 75W

- PHYSICAL

WxDxH: 280x236x143 mm

Weight: 5,4 Kg.