

COMPACTBAR WB 100cm (it. 212315)



Specifiche tecniche

LED type	CW+WW (5W)
Number of LEDs	18 (2700K) + 18 (6500K)
Lumen MAX	8100
Lenses	8° 15° 15° x 30° 25° 40° 60°
Filters	None f 80° f 100° f 8°x 60°
Control type	Protocol USITT DMX512 - RDM Protocol USITT DMX512 - RDM + Wireless (on request) DALI DT6
Functions	RDM/DRS
Input range	iv 200 - 240 VAC; 47/63 Hz
Power (W)	70
Inrush current	3A@230V
IP protection rating	IP 67
Sizes l x p x h (mm)	1035 x 71 x 115
Weight (Kgs)	4
Mounting systems	Surface Truss (optional)

Colour finishing	Standard Grey Black RAL 9005 (optional) White (optional)
Marine Grade treatment	None Yes
Product Category	Linear Bar

La tua configurazione

LED type	CW+WW (5W)
Number of LEDs	18 (2700K) + 18 (6500K)
Lumen MAX	8100
Lenses	8°
Filters	None
Control type	Protocol USITT DMX512 - RDM
Input range	iv 200 - 240 VAC; 47/63 Hz
Power (W)	70
Inrush current	3A@230V
IP protection rating	IP 67
Sizes l x p x h (mm)	1035 x 71 x 115
Weight (Kgs)	4
Mounting systems	Surface
Colour finishing	Standard Grey
Marine Grade treatment	None
Product Category	Linear Bar