

COMPACTBAR WB 50cm (it. 212312)



Specifiche tecniche

LED type	CW+WW (5W)
Number of LEDs	9 (2700K) + 9 (6500K)
Lumen MAX	4050
Lenses	8° 15° 15° x 30° 25° 40° 60°
Filters	None f 80° f 100° f 8°x 60°
Control type	Protocol USITT DMX512 - RDM Protocol USITT DMX512 - RDM + Wireless (on request) DMX - RDM + DALI DMX - RDM + DALI + Wireless
Functions	RDM/DRS
Input range	iv 200 - 240 VAC; 47/63 Hz
Power (W)	35
Inrush current	0,15A@230V
Tilt	160°
IP protection rating	IP 67
Sizes l x p x h (mm)	540 x 71 x 115
Weight (Kgs)	2,5

Mounting systems	Surface Truss (optional)
Colour finishing	Standard Grey Black RAL 9005 (optional) White (optional)
Marine Grade treatment	None Yes
Product Category	Linear Bar

La tua configurazione

LED type	CW+WW (5W)
Number of LEDs	9 (2700K) + 9 (6500K)
Lumen MAX	4050
Lenses	8°
Filters	None
Control type	Protocol USITT DMX512 - RDM
Input range	iv 200 - 240 VAC; 47/63 Hz
Power (W)	35
Inrush current	0,15A@230V
Tilt	160°
IP protection rating	IP 67
Sizes l x p x h (mm)	540 x 71 x 115
Weight (Kgs)	2,5
Mounting systems	Surface
Colour finishing	Standard Grey
Marine Grade treatment	None
Product Category	Linear Bar