

art. 1506
PARLED 100 RGBW/FC

Studio Due

emotion and creativity in light



ParLed 100

rgbw/fc

PARLED 100 RGBW/FC flood projector for indoor use. Suitable for touring, tv studios, venues, theatres and generally for the entertainment market. Easy setup and configuration of the fixture by control panel with push buttons.

- Standard fixture colour finishing is grey.

TECHNICAL FEATURES

- **SOURCE**
n. 7 RGBW/FC LEDs
Total out lumen: R 500lm, G 820lm, B 150lm, W 1050lm
- **OPTIC**
25° standard beam (32mm lenses)
On request: narrow, wide (32mm lenses)
- **TILT**
Manual 360°
- **CONTROL**
Standard interface: RS-485
Protocol: USITT DMX 512
- **CONNECTIONS**
Signal: XRL 5pin (on request 3pin) male-female connector
Main Power: 3x1mm cable
- **SETUP AND CONFIGURATION**
Control panel with 4 push buttons (on the rear of the fixture)
LED display with flip function (on the rear of the fixture)
Remote configuration by DRS Setup device
Dedicated DMX channel for white balance
DMX or automatic mode with MASTER/SLAVE function
Intelligent temperature control
Flicker free function
Smooth dimming function
Halogen simulation
CYM emulation
- **SAFETY**
eyebolts for safety chain
- **IP 20 RATING PROTECTION**
- **POWER SUPPLY**
Voltage range: 100-240VAC
Frequency range: 47-63Hz
Active Power factor:
PF>0.91/230VAC, PF>0.98/120VAC
Current: 0.22A@230VAC, 0.38A@120V
Power: 45W
- **DMX CHANNELS**
- 9 ch mode
- 5 ch mode
- 4 ch mode
- **PHYSICAL**
WxDxH: 185x140x230mm
Weight: 2 Kg.



Click on the QR Code with your smartphone to go directly to the fixture website page

PHYSICAL



© Copyright 2014 Studio Due light srl
Strada Poggino, 100
01100 Viterbo (Italy)
tel. +39.0761.352520 (4 lines)
fax +39.0761.352653
C.F. e P. IVA 05793121004

Specifications are subject to change without notice. Trademarks are the property of Studio Due Light Srl
www.studiodue.com