







The new T- BRIGHT family becomes smaller and powerful. Designed to minimize the dimensions of a LED lighting fixture keeping an high level of lumen package in a very compact design. The T-BRIGHT PLUS RGBW/FC is particularly adapt for touring, tv studios, venues, theatres and generally for the architainment market.

• Standard fixture colour finishing is black. Optional grey and white (art. FX-COLOUR).

## **TECHNICAL FEATURES**

### SOURCE

n. 45 RGBW-FC CREE XML High Power 16W LEDs Total light power: 340W

Total out lumen: R 4000, G 6100, B 1200, W 8100

## OPTIC

Square Open 20°x30° (35mm lenses) On request:

- narrow, wide 35mm lenses

# TILT

Manual 160°

### CONTROL

Standard interface: RS-485, optocoupled input Protocol: USITT DMX512

## CONNECTIONS

Signal: XRL 5pin (on request 3pin) IP 64 connector (male-female) possibility to link up to 32 devices in chain

Available as accessories: - Wireless DMX receiver

Main Power: POWERCON 3pin IP 64

connector (male-female)

possibility to link up to 6 devices at 230V or

3 devices at 120V in chain.



Click on the QR Code with your smartphone to go directly to the fixture website page

## SETUP AND CONFIGURATION

Control panel with touch technology and led display with flip function

or by DRS (remote control device)

Dedicated DMX channel for white balance DMX or Auto mode with Master-Slave function

Intelligent temperature control

Halogen simulation

CYM simulation

Flicker-free function

Smooth dimming function

 RATING PROTECTION IP 64

## DMX CHANNELS

- 9CH mode
- 6CH mode
- 5CH mode
- 4CH mode

## POWER SUPPLY

Voltage range: 100-240VAC Frequency range: 47-63Hz Active Power factor: 0,95

Current:

1.5A@230VAC, 3.5A@120V

Power: 350W Fuse T8A (inside fixture)

## PHYSICAL

WxDxH: 425x160x365 mm

Weight: 9,8 Kg.

# Studio Due emotion and creativity in light







© Copyright 2014 **Studio Due light** srl Strada Poggino, 100 01100 Viterbo (Italy) tel. +39.0761.352520 (4 lines) fax +39.0761.352653 C.F. e P. IVA 05793121004