

art. 1507
PARLED 100 DRS RGBW/FC

Studio Due

emotion and creativity in light



ParLed 100 drs rgbw/fc

This IP 67 flood projector, has the same features of the art. 1506 except the control panel. Configuration of the fixture by DRS Setup device.

- Standard fixture colour finishing is grey.

TECHNICAL FEATURES

- **SOURCE**

n. 7 RGBW/FC LEDs
Total out lumen: R 500lm, G 820lm, B 150lm, W 1050lm

- **OPTIC**

25° standard beam (32mm lenses)
On request: narrow or wide (32mm lenses)

- **TILT**

Manual 360°

- **CONTROL**

Standard interface: RS-485
Protocol: USITT DMX 512

- **CONNECTIONS**

Signal: XRL 5pin (on request 3pin) male-female connector
Main Power: 3x1mm cable

- **SETUP AND CONFIGURATION**

Remote configuration by DRS Setup device
Dedicated DMX channel for white balance
DMX or automatic mode with MASTER/SLAVE function
Intelligent temperature control
Flicker free function
Smooth dimming function
Halogen simulation
CYM emulation

- **SAFETY**

eyebolts for safety chain

- **IP 67 RATING PROTECTION**

- **POWER SUPPLY**

Voltage range: 100-240VAC

Frequency range: 47-63Hz

Active Power factor:

PF>0.91/230VAC, PF>0.98/120VAC

Current: 0.22A@230VAC, 0.38A@120V

Power: 45W

- **DMX CHANNELS**

- 9 ch mode

- 5 ch mode

- 4 ch mode

- **PHYSICAL**

WxDxH: 185x140x230mm

Weight: 2 Kg.



Click on the QR Code with your smartphone to go directly to the fixture website page

PHYSICAL



© Copyright 2014 Studio Due light srl
Strada Poggino, 100
01100 Viterbo (Italy)
tel. +39.0761.352520 (4 lines)
fax +39.0761.352653
C.F. e P. IVA 05793121004