

## MEGAWHITE 66 M (it. 210210)



### Specifiche tecniche

LED type	WHITE 2700 WHITE 4000 WHITE 6500 RED GREEN BLUE AMBER
Number of LEDs	66
Lumen MAX	32000
Lenses	4° 8° 10°x30° 15° 25° 40° 60°
Connectors and cables	Main Power: 3x1,5mm cable DMX signal: 4pin IP67 connector (male-female)
Control type	Protocol USITT DMX512 - RDM Protocol USITT DMX512 - RDM + Wireless (on request)
Functions	Dedicated DMX channel for white balance from 2700K to 6500K DMX or Auto Mode with Master-Slave function Intelligent temperature control Smooth dimming function Ultrafast strobe effect Halogen simulation Flicker-free function
Setup	RDM/DRS
DMX channels	3ch - 1ch

Input range	100 - 277 VAC; 47/63 Hz
Power (W)	240
Current	1,1A@230VAC
Power Factor	PF>0,95@230VAC
Inrush current	80A@230V
IP protection rating	IP 67
Operating temperature	-30°C +45°C
Sizes l x p x h (mm)	640x162x320
Weight (Kgs)	15 Kg.
Materials	Ultra clear 4mm tempered glass PMMA lenses All aluminium alloy Polyester powder coated
Mounting systems	Surface Truss (optional)
Colour finishing	Standard Grey Black RAL 9005 (optional) White RAL 9010 (optional) Any RAL (optional)
Marine Grade treatment	None Yes
Product Category	Wall Washer
Accessories - Anti glare	None Yes
Accessories - Barn door	None Yes

## La tua configurazione

LED type	WHITE 2700
Number of LEDs	66
Lumen MAX	32000
Lenses	4°
Control type	Protocol USITT DMX512 - RDM
Input range	100 - 277 VAC; 47/63 Hz
Power (W)	240
Current	1,1A@230VAC
Power Factor	PF>0,95@230VAC
Inrush current	80A@230V
IP protection rating	IP 67
Operating temperature	-30°C +45°C
Sizes l x p x h (mm)	640x162x320
Weight (Kgs)	15 Kg.
Mounting systems	Surface
Colour finishing	Standard Grey
Marine Grade treatment	None
Product Category	Wall Washer
Accessories - Anti glare	None
Accessories - Barn door	None