



## 1 Fixture Color

Blue/Silver	Black
L1.0033520 Orbiter without Yoke, Cable, etc.	L1.0033521 Orbiter black without Yoke, Cable, etc.

Each version includes a RF antenna and protective cap

## 2 Yoke Type

MAN	P.O.
L2.0034025 Manual Yoke with Spigot	L2.0036642 P.O. Yoke with Spigot

Each version includes a 28 mm Junior Pin

## 3 AC Cables

Inline Switch & Connector (MAN)	1.5 m Bare Ends (P.O.)
L2.0024627 Bare Ends (3 m) L2.0001486 Schuko (3 m) L2.0001487 Edison (7 m) L2.0003678 Chinese (3 m) L2.0008904 Japanese (3 m)	L2.0001485 Bare Ends (1.5 m)

P.O. version without line switch and connector

## 4 Control

Incl. Control Panel	Without Control Panel
L2.0033732 Control Panel* L2.0033799 5 m Cable for Control Panel L2.0033800 15 m Cable for Control Panel	<b>Network Control ONLY!</b>

\*Without cable, includes a carrying pouch, lanyard and D-ring

## 5 Optic

Open Face	Dome	Softbox
L2.0033542 Open Face Optic 60° L2.0033541 Open Face Optic 30° L2.0033540 Open Face Optic 15°	L2.0034266 DoPchoice Dome S L2.0034267 DoPchoice Dome M L2.0034268 DoPchoice Dome L L2.0034621 Chimera Dome M L2.0034622 Chimera Dome L	L2.0033840 DoPchoice SnapBag S L2.0034270 DoPchoice SnapBag M L2.0034269 DoPchoice Octa 4 L2.0033839 Chimera Lightbank S L2.0036058 Chimera Lightbank M L2.0034271 Chimera Octa 4

## 6 Accessories for Open Face

Open Face 30° or 60°	Open Face 15°
L2.79470.0 4-leaf barndoor (168 mm / 6.6") L2.79500.0 8-leaf barndoor (168 mm / 6.6") L2.79480.0 Snoot (168 mm / 6.6")	L2.39870.0 4-leaf barndoor (245 mm / 9.7") L2.39900.0 8-leaf barndoor (245 mm / 9.7") L2.79880.0 Snoot (245 mm / 9.7")

## 7 Transport

Case	Bag
L2.0034626 Case for Orbiter	L2.0034624 Bag for Orbiter Open Face Optics

## 8 Miscellaneous

Skid	Frames	Safety
L2.0034272 Skid for Orbiter	L2.0033797 Four Unit Frame L2.0033798 Six Unit Frame	L2.0008899 Safety cable (3 mm) 0,6 m, max. load 5 kg L2.0020919 Safety cable (4 mm) 1 m, max. load 16 kg L2.0007590 Safety cable (5 mm) 1 m, max. load 25 kg