

PARLED 100/M DRS (Monochromatic)



art. 1509

Short description

PARLED 100/M DRS MONOCHROMATIC. IP 67 compact flood projector.

Configuration of the fixture by DRS Setup device.

This monochromatic version can be used to decorate columns, pillars, along walkways, on patios, in steps, to highlight and to landscape details and key elements.

- Colour finishing is grey. No other colours available.

Description

• SOURCE

n. 7 high power 5000K White LEDs

Total out lumen: 4000lm (white LEDs 5000K)

Total light power: 34W

On request:

3000K, 4000K, 6000K white LEDs or red, green, blue, amber LEDs

• OPTIC

25°; standard beam (32mm lenses)

On request: narrow, wide (32mm lenses)

PARLED 100/M DRS (Monochromatic)

- TILT

Manual 360°;

- CONNECTIONS

Signal: 4pin IP 67 male-female connector

Main Power: 3x1mm cable 1,5mt.

- SETUP AND CONFIGURATION

Remote configuration by DRS Setup device

Intelligent temperature control

Flicker free function

Smooth dimming function

Halogen simulation

- SAFETY

eyebolts for safety chain

- IP 67 RATING PROTECTION

- POWER SUPPLY

Voltage range: 100-240VAC

Frequency range: 47-63Hz

Active Power factor:

PF>0.90/230VAC, PF>0.98/120VAC

Current: 0.2A@230VAC, 0.3A@120V

Power consumption: 38W

- DMX CHANNELS

- 3 ch mode

- 1 ch mode

- PHYSICAL

WxDxH: 185x140x230mm

Weight: 2 Kg.