

TERRA WL5 24V WB (it. 210460)



Specifiche tecniche

LED type	CW+WW (5W)
Number of LEDs	5 (2700K) + 5 (6500K)
Lumen MAX	2200
Lenses	8° 15° 15° x 30° 25° 40° 60°
Filters	None f 17° tilt f34° tilt f 60° f 65° f 100° f 8°x 60°
Connectors and cables	Combo-cable 2x1mm Red-Black + 2x0.25mm shielded + 1x1mm Earth - cable 0.6mt
Control type	Protocol USITT DMX512 - RDM
Functions	Dedicated DMX channel for white balance from 2700K to 6500K DMX or Auto Mode with Master-Slave function Intelligent temperature control Continuous dimming 0-100% Smooth dimming function Halogen simulation Flicker-free function
Setup	RDM/DRS
Input range	20 - 48 VDC
Power (W)	16 W

IP protection rating	IP 67 68 optional
IK grade protection	08
Dimensions d x h (mm)	190 x 52,5
Weight (Kgs)	2,7
Materials	Ultra clear 10mm tempered glass All in stainless steel AISI304
Mounting systems	Inground
Colour finishing	Stainless steel
Marine Grade treatment	None Yes
Product Category	Inground

La tua configurazione

LED type	CW+WW (5W)
Number of LEDs	5 (2700K) + 5 (6500K)
Lumen MAX	2200
Lenses	8°
Filters	None
Control type	Protocol USITT DMX512 - RDM
Input range	20 - 48 VDC
Power (W)	16 W
IP protection rating	IP 67
IK grade protection	08
Dimensions d x h (mm)	190 x 52,5
Weight (Kgs)	2,7
Mounting systems	Inground
Colour finishing	Stainless steel
Marine Grade treatment	None
Product Category	Inground