

TERRA WL5 POB M (it. 210310)



Specifiche tecniche

LED type	WHITE 2700 WHITE 4000 WHITE 6500 RED GREEN BLUE AMBER
Number of LEDs	10
Lumen MAX	2500
Lenses	8° 15° 15° x 30° 25° 40° 60°
Filters	None f 17° tilt f 34° tilt f 60° f 65° f 100° f 8°x 60°
Connectors and cables	Main Power: 3x1mm cable DMX signal: 2xAWG24 + shield cable 0,6mt.
Control type	Protocol USITT DMX512 - RDM Protocol USITT DMX512 - RDM + Wireless (on request)

Functions	DMX or Auto Mode with Master-Slave function Intelligent temperature control Continuous dimming 0-100% Smooth dimming function Halogen simulation Flicker-free function
Setup	RDM/DRS
DMX channels	3ch - 1ch
Input range	100 - 277 VAC; 47/63 Hz
Power (W)	18
IP protection rating	IP 67 68 optional
IK grade protection	08
Dimensions d x h (mm)	190 x 74,6
Weight (Kgs)	4
Materials	Ultra clear 10mm tempered glass All in stainless steel AISI304
Mounting systems	Inground
Colour finishing	Stainless steel
Marine Grade treatment	None Yes
Product Category	Inground

La tua configurazione

LED type	WHITE 2700
Number of LEDs	10
Lumen MAX	2500
Lenses	8°
Filters	None
Control type	Protocol USITT DMX512 - RDM
Input range	100 - 277 VAC; 47/63 Hz
Power (W)	18
IP protection rating	IP 67
IK grade protection	08
Dimensions d x h (mm)	190 x 74,6
Weight (Kgs)	4
Mounting systems	Inground
Colour finishing	Stainless steel
Marine Grade treatment	None
Product Category	Inground