

## TERRA WL5 POB WB (it. 210430)



### Specifiche tecniche

LED type	CW+WW (5W)
Number of LEDs	5 (2700K) + 5 (6500K)
Lumen MAX	2200
Lenses	8° 15° 15° x 30° 25° 40° 60°
Filters	None f 17° tilt f34° tilt f 60° f 65° f 100° f 8°x 60°
Connectors and cables	Main Power: 3x1mm cable DMX signal: 2xAWG24 + shield cable 0,6mt.
Control type	Protocol USITT DMX512 - RDM Protocol USITT DMX512 - RDM + Wireless (on request)
Functions	Dedicated DMX channel for white balance from 2700K to 6500K DMX or Auto Mode with Master-Slave function Intelligent temperature control Continuous dimming 0-100% Smooth dimming function Halogen simulation Flicker-free function
Setup	RDM/DRS

DMX channels	4ch - 2ch - 1ch
Input range	100 - 277 VAC; 47/63 Hz
Power (W)	18
IP protection rating	IP 67 68 optional
IK grade protection	08
Dimensions d x h (mm)	190x74,6
Weight (Kgs)	4,0
Materials	Ultra clear 10mm tempered glass All in stainless steel AISI304
Mounting systems	Inground
Colour finishing	Stainless steel
Marine Grade treatment	None Yes
Product Category	Inground

## La tua configurazione

LED type	CW+WW (5W)
Number of LEDs	5 (2700K) + 5 (6500K)
Lumen MAX	2200
Lenses	8°
Filters	None
Control type	Protocol USITT DMX512 - RDM
Input range	100 - 277 VAC; 47/63 Hz
Power (W)	18
IP protection rating	IP 67
IK grade protection	08
Dimensions d x h (mm)	190x74,6
Weight (Kgs)	4,0
Mounting systems	Inground
Colour finishing	Stainless steel
Marine Grade treatment	None
Product Category	Inground